



NON-RETURN VALVES

JV6820

WAFER PATTERN SWING CHECK VALVE



Part No. JV6820E - EPDM Seat (Standard)

Part No. JV6820N - NBR Seat

Part No. JV6820V - Viton Seat

Part No. JV6820P - PTFE Seat

STAINLESS STEEL BODY TO FIT BETWEEN PN10/16* FLANGES

*DN300 - PN10 only

SIZE	50	65	80	100	125	150	200	250	300
A	32	40	54	70	92	112	154	200	240
B	14	14	14	18	18	20	22	26	32
C	109	128	145	164	195	221	275	330	380
D	35	48	60	78	98	117	160	200	235
Weight Kg	0.9	1.2	1.5	2.5	3.2	5.3	9.7	16.2	28

These economical stainless wafer type check valves are suitable for various applications. They can be fitted in the horizontal position or in the vertical position with the flow going upwards. These valve requires a low minimum pressure to open.

Features & Benefits

- Suitable for upward & horizontal flow
- Space saving
- Low head losses

Pressure & Temperature

Pressure range:-
PN25 Rated

Temperature Range:-
EPDM Seat: 0°C to 130°C
NBR Seat: 0°C to 95°C
Viton Seat: 0°C to 200°C
PTFE Seat: 0°C to 200°C

MATERIALS

Body	Stainless Steel (316)
Disc	Stainless Steel (316)
Screw	Stainless Steel (316)
Seat	EPDM (Standard) / NBR / Viton / PTFE