


t +44 (0) 23 8066 9666 f +44 (0) 23 8066 9606 sales@johnsonvalves.com www.johnsonvalves.com

Data Sheet 19.01



LEVEL & SIGHT INDICATORS

572

TANK LEVEL INDICATORS



Part No 572

BRONZE SELF-CLOSING (PUSH BUTTON TYPE)

The 572 set of bronze gauge cocks are generally used for small oil and fuel tanks in the marine industry offering the added safety of a spring loaded self-closing valve on the bottom fitting which prevents leakage in the event of a sight glass breakage.

| SIZE | DN15 |
|----------------|------|
| BSP CONNECTION | 1/2 |
| TUBE DIAMETER | 12 |
| A | 30 |
| В | 58 |
| С | 48 |
| D | 13.5 |
| E | 51 |
| F | 12 |

| MATERIALS | |
|--------------------|-----------------|
| Body | Bronze LG2 |
| Screw Plug | Brass |
| Gland & Gland Nut | Brass |
| Stem & Push Button | Brass |
| Spring | Stainless Steel |
| O-Ring | FPM |
| Plug Washer | PTFE |

Features & Benefits

- Self-closing to prevent leakage in the event of a sight glass breakage.
- Sight glass & evolite tube cut to size if required.
- Brass tube guard protectors available.
- Spare sealing rings available.

Pressure & Temperature

Pressure range:-Up to 16 Bar.

Temperature Range:-0°C to 100°C.

WHEN GLASS TUBE AND GUARDS ARE REQUIRED IT IS NECESSARY TO STATE THE DISTANCE BETWEEN THE CENTRES AT WHICH THE GAUGES ARE TO BE FITTED