



**1060A**  
Bronze  
Metal Disc  
Swing Type  
Check (Non-Return) Valve  
BSP Threaded



Pegler Yorkshire



This bronze swing type check valves is suited for steam, water and oil applications. It can be fitted in the horizontal position or in the vertical position with the flow going upwards. This valve requires a low minimum pressure to open.

**Approvals, Features & Benefits**

- BS5154 Series B
- Suitable for air, oil, steam & water
- Cracking pressure 0.5 - 1 bar
- High quality construction
- Metal seat

**Pressure & Temperature**

Pressure range:-  
PN25 Rated

Temperature Range:-  
25 bar @ -10°C to 100°C  
10.5 bar @ 186°C

BSPP	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
<b>A</b>	62	76	83	94	105	125	161	172	222
<b>B</b>	45	55	60	65	75	90	112	132	130
<b>Weight Kg</b>	0.38	0.58	0.86	1.26	1.66	2.66	3.44	4.52	8.38

MATERIALS	
<b>Body</b>	Bronze
<b>Cap</b>	Bronze (1/2" - 2"), Brass (2 1/2" - 4")
<b>Swinger</b>	Brass (1/2" - 1"), Bronze (1 1/4" - 4")
<b>Swinger Pin</b>	Brass
<b>Swing Pin Cap (2 1/2" - 4" only)</b>	Brass
<b>Nut</b>	Brass