



**JV081013**  
(Model 237)  
**Ductile Iron Body**  
**Spring-Loaded**  
**Double**  
**Check (Non-Return) Valve**  
**Flanged**  
**PN16**



WRAS approved spring-loaded double check (non-return valve) suitable for potable water applications.

This valve can be installed in both horizontal and vertical lines with upward flow or in any intermediate position.

**Approvals, Features & Benefits**

- WRAS approved\*
- Double check
- Can be installed in any position
- Epoxy coat finish

\* DN250-300 WRAS approved materials only

**Pressure & Temperature**

Pressure range :-  
PN16

Temperature range:-  
-10°C to 85°C

DN (A)	50	65	80	100	125	150	200	250	300
<b>B</b>	165	185	200	220	250	285	340	405	460
<b>C</b>	203	243	283	343	403	463	579	711	823
<b>Kv</b>	89.9	109.7	133.9	240.2	375.8	540.0	963.4	-	-
<b>Weight Kg</b>	16.6	21	27	35	57	78	106	160	250

<b>MATERIALS</b>	
<b>Body</b>	Ductile Iron (DN250-300 Cast Iron)
<b>Disc</b>	Ductile Iron (DN250-300 Cast Iron)
<b>Disc Trim</b>	EPDM
<b>Spring</b>	Stainless Steel