



**JV081023**  
**Bronze**  
**Short Pattern**  
**Marine Swing Type**  
**Check (Non-Return) Valve**  
**Flanged**  
**PN16**



A marine quality swing type check (non-return valve) with PN10/16 flange ends.

This valve can be fitted in the horizontal position or in the vertical position with the flow going upwards.

**Approvals, Features & Benefits**

- 3.1 material certificates on request
- Suitable for seawater, air, oil, steam & water
- High quality construction
- NBR O-ring
- Short compact pattern

**Pressure & Temperature**

Pressure range :-

DN15 - D150 : PN16  
DN200 - D300 : PN10

Temperature range:-  
-40°C to 100°C

DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300
<b>L</b>	65	65	70	75	80	85	105	125	145	170	200	255	310	360
<b>B</b>	26	26	26	26	26	26	26	30	32	36	38	42	48	50
<b>B1</b>	14	14	14	14	14	16	16	18	20	22	22	22	24	24
<b>D</b>	95	105	115	140	150	165	185	200	220	250	285	340	395	445
<b>Flange</b>	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN10	PN10	PN10
<b>Weight Kg</b>	2.1	2.5	3.0	5.0	6.0	7.0	9.0	11.0	16.0	21.0	29.0	44.0	64.0	79.0

**MATERIALS**

<b>Body</b>	Bronze (LG2)
<b>Disc</b>	Bronze (LG2)
<b>Flap</b>	Ali-Bronze (CuAl10 Ni)
<b>O-ring</b>	NBR