



## JV081028

**Bronze**  
**NBR Seals**  
**Swing Type**  
**Check (Non-Return) Valve**  
**Length B**  
**Multi-Flange Wafer Type**  
**PN10/16**



A marine quality aluminium bronze spring loaded flap type check (non-return) valve used to prevent backflow in water and seawater systems and can be used in other applications providing the valve materials are compatible with the media.

It can be fitted in the horizontal position or in the vertical position with the flow going upwards.

### Approvals, Features & Benefits

- Marine quality construction
- NBR seals (other materials available)
- Suitable for upward & horizontal flow
- Space saving
- Low head losses

### Pressure & Temperature

Pressure range:-

DN40-200 : PN16 Rated  
DN250-600 : PN10 Rated

Temperature Range:-

-15°C to 80°C

DN	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600
<b>A</b>	22	30	37	48	70	95	121	155	196	230	250	303	358	398	480
<b>B</b>	16	16	16	16	16	18	19	29	29	38	41	51	51	61	71
<b>C</b>	94	109	129	144	164	194	220	275	330	380	440	491	541	596	698
<b>Weight Kg</b>	0.8	1.1	1.6	2.0	2.4	3.3	4.5	10	16	28	35	60	68	80	120

### MATERIALS

<b>Body</b>	Bronze
<b>Disc</b>	Bronze
<b>O-rings</b>	NBR
<b>Screw</b>	Stainless Steel
<b>Eyebolt</b>	Stainless Steel