



JV100009

**Stainless Steel
Viton Lined
Butterfly Valve**

**Multi-Flange Wafer Type
PN6/10/16, ANSI150, BST D & E**



A stainless steel body and disc with Viton liner makes this valve a cost effective solution for a wide variety of higher temperature isolation applications.

The butterfly valve offers quick opening and closing with full flow in either direction and leak tight shut off.

Flange gaskets not needed since the lining that extends onto the faces acts as a gasket.

Approvals, Features & Benefits

- Viton lined for higher temperature duties
- Lightweight construction
- ISO 5211 top for direct mount actuation
- Lever operated as standard
- Gearbox operated on request

Pressure & Temperature

Pressure range :-
PN16

Temperature range :-
-10°C to 150°C

DN	50	65	80	100	125	150	200
A	43	46	46	52	56	56	60
B	89	102	118	150	174	205	260
C	62	69	90	106	119	131	166
D	126	136	150	170	180	200	230
E	170	170	206	206	285	285	400
F	50	50	69	69	90	90	72
ISO 5211	F05	F05	F05	F05	F07	F07	F10
Torque (Nm)*	16.25	26.25	35	55	85	123.75	202.5
Weight Kg	2.1	2.4	3.1	4.1	6.1	7.5	14.1

* Torque calculated at 16 Bar wet duty, pressure includes 25% safety, add 25% for dry duty.

KV Rates	10° Opening	20° Opening	30° Opening	40° Opening	50° Opening	60° Opening	70° Opening	80° Opening	90° Opening
DN50	0.05	2.6	6	13	23	38	60	91	99
DN65	0.09	3.8	14	33	53	75	98	108	108
DN80	0.17	7.8	16	34	60	100	158	237	261
DN100	0.26	15	31	67	120	199	314	471	518
DN125	0.43	25	53	115	205	339	535	803	883
DN150	0.69	39	82	177	316	522	827	141	1364
DN200	2.6	52	142	250	450	713	1122	1723	2716

MATERIALS

Body	Stainless Steel (CF8M)
Disc	Stainless Steel (CF8M)
Liner	Viton
Shaft	Stainless Steel (AISI 316)
Bushing	PTFE