



PG-VNF
General Purpose
Steel Cased
Pressure & Vacuum Gauges
Direct Mounting
Bottom Entry



A good quality low cost general purpose pressure gauge. Suitable for a wide range of applications where the fluid used is not aggressive to copper alloys.

These gauges can be supplied with certification that confirms conformity to BS EN 837-1 :1998 (formally BS 1780) Accuracy Class 2.5

It is recommended that the pressure range should be chosen so that the working pressure is not more than 65% of the maximum scale value for fluctuating pressures or 75% for steady pressures.

Approvals, Features & Benefits

- Accuracy Class 2.5 EN 837-1
- Accuracy certification on request
- Suitable for various duties
- Economical & reliable
- Dual scale dial as standard
- Calibrated in Bar & PSI
- Bourdon tube type

Pressure & Temperature

Pressure range:-
See table below

Temperature range:-
0 to 60°C*

* Can be used on higher temperatures and steam if a suitable ring or u-syphon is fitted and filled with water prior to use to prevent the media entering the gauge.

A DIAL SIZE	40	50	63	100
B	41	52	64	106
C	23	27	29	40
D	58	67	85	134
Connection BSP	1/8	1/8	1/4	3/8
Weight Kg	0.10	0.15	0.18	0.25

Please Note : All dimensions & weights are approximate, please call sales for further details if they are critical

MATERIALS

Case	Black Steel
Movement	Brass
Socket	Brass
Window	Polycarbonate (100mm Glass)

STANDARD DUAL RANGES (others on request)

0 to -1 Bar & 30" Hg (Vac)	0 to 1 Bar & 15 PSI	0 to 2 Bar & 30 PSI	0 to 4 Bar & 60 PSI	0 to 7 Bar & 100 PSI
0 to 11 Bar & 160 PSI	0 to 14 Bar & 200 PSI	0 to 20 Bar & 300 PSI	0 to 27 Bar & 400 PSI	0 to 41 Bar & 600 PSI
0 to 70 Bar & 1000 PSI	0 to 100 Bar & 1600 PSI			

ASSOCIATED PRODUCTS

Brass Pressure Gauge Isolation Cocks

1/4" • 3/8" • 1/2"
Male x Female • Female x Female



Steel & Brass Pressure Gauge Syphons

1/4" • 3/8" • 1/2"
U-Syphon • Ring (Pig Tail) Syphon



Brass & Stainless Steel Snubbers

1/4" • 3/8" • 1/2"

