



PG-VBF

Traditional Brass Cased Pressure & Vacuum Gauges Back Mounting Flange Bottom Entry



A high quality and robust traditional style Approvals, Features & Benefits general purpose pressure gauge.

These gauges can be supplied with certification that confirms conformity to BS EN 837-1 :1998 (formally BS 1780) Accuracy Class 1.6

It is recommended that the pressure range should be chosen so that the working pressure is not more than 65% of the maximum scale value for fluctuating pressures or 75% for steady pressures.

- Accuracy Class 1.6 EN 837-1
- Accuracy certification on request
- Traditional design
- Dual scale dial as standard
- Calibrated in Bar & PSI
- Bourdon tube type

Pressure & Temperature

Pressure range:-

See table below

Temperature range:-

0 to 60°C*

* Can be used on higher temperatures and steam if a suitable ring or u-syphon is fitted and filled with water prior to use to prevent the media entering the gauge.

A DIAL SIZE	80	100	150
В	98.5	127	184
С	40	42	44
D	114	151	206
CONNECTION BSP	1/4	3/8	3/8
Weight Kg	0.25	0.35	0.45

Please Note: All dimensions & weights are approximate, please call sales for further details if they are critical

MATERIALS	
Case	Brass
Wetted Parts	Brass
Bezel	Brass
Window	Glass

STANDARD DUAL RANGES (others on request)						
Vac & Compound	0 to 30"Hg (-1 Bar)	30"Hg (-1 Bar) to 15 PSI (1 Bar)	30"Hg (-1 Bar) to 30 PSI (2 Bar)	30"Hg (-1 Bar) to 60 PSI (4 Bar)		
	30"Hg (-1 Bar) to 100 PSI (7 Bar)	30"Hg (-1 Bar) to 160 PSI (10 Bar)	30"Hg (-1 Bar) to 200 PSI (14 Bar)	30"Hg (-1 Bar) to 300 PSI (20 Bar)		
Pressure	0 to 15 PSI (1 Bar)	0 to 30 PSI (2 Bar)	0 to 60 PSI (4 Bar)	0 to 100 PSI (7 Bar)		
	0 to 160 PSI (10 Bar)	0 to 200 PSI (14 Bar)	0 to 300 PSI (20 Bar)	0 to 400 PSI (27 Bar)		
	0 to 600 PSI (41 Bar)	0 to 1000 PSI (70 Bar)	0 to 1600 PSI (100 Bar)	0 to 2000 PSI (140 Bar)		
	0 to 3000 PSI (210 Bar)	0 to 4000 PSI (270 Bar)	0 to 6000 PSI (410 Bar)	0 to 10000 PSI (700 Bar)		

ASSOCIATED PRODUCTS

Brass Pressure Gauge Isolation Cocks

1/4" • 3/8" • 1/2" Male x Female • Female x Female



Steel & Brass Pressure Gauge Syphons

1/4" • 3/8" • 1/2" U-Syphon • Ring (Pig Tail) Syphon



Brass & Stainless Steel Snubbers

1/4" • 3/8" • 1/2"

