


31 Steel Cased Bi-Metallic Temperature Gauge 100mm Dial Axial



These temperature gauges have black steel cases with stainless steel bezels, PMMA windows and brass pockets as standard. They combine the benefits of quality and reliability offering an easy to read dial, fast response and accurate temperature indication.

Approvals, Features & Benefits

- Designed to BS EN 13190
- Accuracy class 2
- IP54 Protection (EN 60529:1992)
- Supplied with push-on brass pocket

MODEL	DIAL (A)	RANGE	POCKET LENGTH (B)	C (BSP)	D
31/624/0	100mm	-20 to 60°C&F	50mm	1/2"	12
31/644/0	100mm	-20 to 60°C&F	100mm	1/2"	12
31/664/0	100mm	-20 to 60°C&F	150mm	1/2"	12
31/621/0	100mm	0 to 120°C&F	50mm	1/2"	12
31/641/0	100mm	0 to 120°C&F	100mm	1/2"	12
31/661/0	100mm	0 to 120°C&F	150mm	1/2"	12
31/625/0	100mm	0 to 160°C&F	50mm	1/2"	12
31/645/0	100mm	0 to 160°C&F	100mm	1/2"	12
31/665/0	100mm	0 to 160°C&F	150mm	1/2"	12

MATERIALS	
Case	Black Steel
Bezel	Stainless Steel
Pocket	Brass
Window	PMMA Plastic