




JV241021

L9 Series
Ductile Iron
NBR Lined
Butterfly Valve
c/w JV-E Electric Actuator
Lugged & Tapped Type
PN16



The JV241021 is a general purpose valve with an NBR liner, offering a long life with low maintenance. Self-lubricating bearings ensures perfect guiding and turning of the shaft without seizure or premature wear.

This valve is supplied completely assembled with a JV-E electric actuator which is small, lightweight and compact in design but still offering high output torques.

All valve and actuator packages are tested and issued with certification confirming the actuators functionality before despatch.

Approvals, Features & Benefits

- Suitable for fitting between PN16 flanges
- Epoxy coated body
- Complete assembled package
- Various voltage options
- Manual override on actuator
- Visual position indicator on actuator

Pressure & Temperature

Pressure range:-
16 bar

Temperature range*:-
-10°C to 80°C

DN	25	32	40	50	65	80	100	125	150	200	250	300
A	33	33	33	43	46	46	52	56	56	60	68	78
B	104	110	116	126	136	150	170	180	200	230	266	292
C	51	56	63	62	69	90	106	119	131	166	202	235
PCD	85	100	110	125	145	160	180	210	240	295	355	410
n° x M	4 x M12	4 x M16	4 x M16	4 x M16	4 x M16	8 x M16	8 x M16	8 x M16	8 x M20	12 x M20	12 x M24	12 x M24
E*	125	125	125	125	125	125	125	133	190	209	209	209
F	124	124	124	124	124	124	124	164	157	182	182	182
Op. Time 90° 50/60hz Sec.	13	13	13	13	13	13	13	22/18	28/23	40/33	40/33	40/33
Actuator Type	JV-E05	JV-E05	JV-E05	JV-E05	JV-E05	JV-E05	JV-E05	JV-E10	JV-E16	JV-E28	JV-E40	JV-E50
Weight Kg	3.9	3.9	3.6	4.5	5.4	6.7	8	10.9	17	27.3	42.1	50.6

ACTUATOR SPECIFICATIONS			
Enclosure	IP68 Watertight (IP68 5m 120hr)	Travel Angle	90° ± 5°
Power Supply	110V & 250V AC 50/60Hz / 24V AC 50/60Hz / 24VDC / 380V & 440V 3PH	Casing Material	Aluminium Alloy, Dry Power Polyester Coated
Indicator	Dome Type Mechanical	Terminal Block	Push Button
Limit Switches	2 x Open / 2 x Close, SPDT, 250V AC	Ambient Temperature	-20 to 60°C
Space Heater	110/220V AC Anti-condensation	Mechanism	Scotch-Yoke (JV-E05 - Spur Gear Type)

ACTUATOR OPTIONS	
LC	Local Control (with torque switches) - Available for models JV-E16 to JV-E120
SM	Super Modulating Unit Input / Output 4-20mA, 0-1V, 2-10V, 0-5V & 1-5V all in one unit (Available for 24VDC, 110VAC & 220VAC)
MC	Modulating Control Unit Input / Output 4-20mA (Only available for 110 & 220VAC)

BUTTERFLY VALVE MATERIALS	
Body	Epoxy Coated Ductile Iron
Liner	NBR
Disc	Stainless Steel
Shaft	Stainless Steel