



JV350006

**Bronze
Angled
Storm Valve
c/w Closing Device
DIN HNA Sr 6 Form B
Flanged PN16**



Storm valves also known as scupper valves, are basically swing check valves which can be supplied with or without a closing device.

They are used in sanitary discharge pipelines which have a ship-side exit, and prevent sea water entering the system during heavy sea.

Features, Benefits & Approvals

- Face to face to DIN HNA
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Optional open/shut indicators
- Closing device (without on request)

Pressure & Temperature

Pressure rating:-
PN1

Temperature range:-
-10°C to 125°C

| DN | 50 x 80 | 65 x 100 | 80 x 125 | 100 x 150 | 125 x 175 | 150 x 200 | 200 x 250 |
|-----------|---------|----------|----------|-----------|-----------|-----------|-----------|
| d2 | 80 | 100 | 125 | 150 | 175 | 200 | 250 |
| D | 165 | 185 | 200 | 220 | 250 | 285 | 340 |
| D1 | 200 | 220 | 250 | 285 | 315 | 340 | 395 |
| L | 180 | 200 | 215 | 250 | 290 | 330 | 425 |
| H | 85 | 95 | 115 | 137 | 140 | 140 | 180 |
| H1 (open) | 275 | 305 | 335 | 357 | 382 | 410 | 460 |
| Weight Kg | 20 | 28 | 31 | 45 | 70 | 83 | 116 |

| MATERIALS | |
|---------------|---------------|
| Body/Bonnet | Bronze (LG2) |
| Disc | Bronze (LG2) |
| Fixing Device | Bronze (LG2) |
| Flap | NBR Faced |
| Stem | Brass (CZ121) |

Do you require class approved valves? Contact sales for availability.

