



JV350009

Bronze Straight Horizontal Storm Valve Flanged PN16

Other flange drillings on request



Storm valves also known as scupper valves, are basically swing check valves which can be supplied with or without a closing device.

They are used in sanitary discharge pipelines which have a ship-side exit, and prevent sea water entering the system during heavy sea.

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Optional open/shut indicators
- Supplied with or without closing device

Pressure & Temperature

Pressure rating:-
PN1

Temperature range:-
-10°C to 80°C

| DN | 40 | 50 | 65 | 80 | 100 | 125 | 150 | 200 | 250 | 300 |
|-----------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| A | 178 | 193 | 204 | 224 | 266 | 283 | 321 | 396 | 464 | 500 |
| Weight Kg | 10 | 14 | 18 | 19 | 28 | 46 | 64 | 100 | 155 | 305 |

| MATERIALS | | OPTIONS | |
|-------------|------------------|--------------|--|
| Body/Bonnet | Bronze (LG2) | Bronze (LG4) | |
| Disc | Bronze (LG2) | Bronze (LG4) | |
| Stem | Manganese Bronze | | |
| Flap | Rubber | Leather | |

Do you require class approved valves? Contact sales for availability.



Lloyd's
Register



ClassNK



RINA