



**F3060**  
Cast Steel  
Angled  
Storm Valve  
c/w Closing Device  
  
Flanged  
JIS-5K or JIS-10K



The F3060 is a JIS specification storm valve supplied with a closing device.

It is used in sanitary discharge pipelines which have a ship-side exit, and prevent sea water entering the system during heavy sea.

**Features, Benefits & Approvals**

- JIS 5K or JIS 10K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Closing device

**Pressure & Temperature**

Test pressure:-  
5.1 kgf/m<sup>2</sup>

Temperature range:-  
-10°C to 60°C

DN	50	65	80	100	125	150	200
<b>A</b>	170	200	220	250	270	310	400
<b>B</b>	90	110	120	130	150	170	190
<b>Flange Dia. (5K)</b>	130	155	180	200	235	265	320
<b>Flange Dia. (10K)</b>	155	175	185	210	250	280	330
<b>Weight Kg</b>	13	19	24	35	50	67	111

<b>MATERIALS</b>	
<b>Body/Bonnet</b>	Cast Steel
<b>Disc</b>	Bronze
<b>Stem</b>	Brass
<b>Flap</b>	NBR Faced

Do you require class approved valves? Contact sales for availability.

