



STEAM TRAPS

FTGS14

SPIRAX SARCO BALL FLOAT STEAM TRAP



Part No. FTGS14

STAINLESS STEEL BODY WITH BSP THREADED CONNECTIONS

SIZE	DN15	DN20
A	121	121
B	107	107
B1	96	96
C	77	77
D	158	158

The FTGS14 is a maintainable ball float steam trap with integral automatic air venting facility. It is available with horizontal connections and has a stainless steel body and an electroless nickel plated SG iron cover offering increased resistance to erosion.

All FTGS14's are provided with a drilled, tapped and plugged hole, therefore a steam lock release (SRL) valve can be retrofitted to the standard trap.

Features & Benefits

- Robustly manufactured.
- Unaffected by water hammer, superheat or vibration.
- Large discharge capacity.
- Reliable performance.
- Dimensionally interchangeable with FT14.

Pressure & Temperature

Pressure range:-

FTGS14/4.5 4.5 Bar.
FTGS14/ 10 10 Bar.
FTGS14/ 14 14 Bar.

Temperature Range:-

0 to 235°C.

MATERIALS	
Body	Austenitic Stainless Steel
Cover Bolts	Steel
Cover	SG Iron (Nickel Plated)
Main Valve Seat	Stainless Steel
Ball Flow & Lever	Stainless Steel
Air Vent Assembly	Stainless Steel

AVAILABLE SPARES
Maintenance Kit
Containing:- Main Valve Assembly, Air Vent Assembly & Set of Gaskets
Main Valve Assembly
Air Vent Assembly
Cover Gasket (Packet of 3)
Steam Lock Release