



AIR VENTS

AE30

SPIRAX SARCO AUTOMATIC AIR VENT



Part No. AE30

BRASS BODY WITH BSP THREADED CONNECTIONS

MODEL	AE30	AE30A	AE30B	AE30C
INLET (BSP)	1/2	1/2	1/2	1/2
DISCHARGE (BSP)	1/4	1/4	1/4	1/4
A	56	56	56	56
B	105	105	105	105
C	10	10	10	10
D	-	-	155	155

The AE30 is a robustly constructed air vent particularly suited for industrial applications. Available with an optional check and lock shield isolation valves.

These vents should be installed in the vertical position, on the air separator, on manifolds, on riser pipes and generally in parts of the system where a concentration of air pockets is to be expected.

Features & Benefits

- Suitable industrial applications.
- Reliable performance.
- Simple float operation.
- Spares available.

Pressure & Temperature

Pressure range:-

Up to 8 bar.

Temperature Range:-

0 to 110°C.

MATERIALS	
Body	DZR Brass
Cover	DZR Brass
Float	Stainless Steel
Lever Stem	Stainless Steel
Valve Cone	EPDM
Valve Seat	Stainless Steel

AVAILABLE SPARES
Maintenance Kit.
Containing:- Valve cone, float, cap 'O' ring, check valve ball and check valve circlip.

Options Available

AE30	Air Vent Only
AE30A	Air Vent With Check Valve
AE30B	Air Vent With Lock Shield Valve
AE30C	Air Vent With Check & Lock Shield Valve