



LEVEL & SIGHT INDICATORS

SG

**SPIRAX SARCO
SIGHT GLASS**



Part No SG

BRASS / BRONZE BODY WITH BSP THREADED CONNECTIONS

SIZE	DN15	DN15	DN20	DN20	DN25	DN25	DN32	DN40	DN50
BSP	1/2	1/2	3/4	3/4	1	1	1 1/4	1 1/2	2
WINDOW	Single	Double	Single	Double	Single	Double	Double	Double	Double
A	89	89	89	89	87.5	89	108	108	114
B	32	32	35	32	38	35	51	51	57
C	50	50	50	50	50	50	50	50	50

The SG sight glass is robustly manufactured and is suitable for detecting flow of many industrial fluids.

The sight glass has a smooth concentric reduction in the inlet connection which promotes turbulence in the sight glass when the fluid passing through it. The turbulent flow inside the sight glass permits any fluid to be detected.

A double window version is available for high luminosity and easy inspection

Features & Benefits

- Robustly manufactured.
- No rotating parts.
- No maintenance.
- Easy & quick inspection.
- Spare windows available.

Pressure & Temperature

3.5 Bar at 148°C.

5 Bar at 0°C to 90°C.

MATERIALS

Body (DN15 to DN25)	Brass
Body (DN32 to DN50)	Bronze
Bezel	Brass
Window	Toughened Soda Lime Glass

AVAILABLE SPARES

Set Of Windows & Gaskets

Set Of Gaskets