



SELF CLOSING VALVES

261002/4

ANGLED PATTERN SELF CLOSING VALVES



Part No. 261002 - Ductile Iron Body with Stainless Steel Trim

Part No. 261004 - Ductile Iron Body with Stainless Steel Trim & Blocking Device

This self closing valve has a spring return mechanism. Used in applications where positive return to the shut-off position is required after the valve is manually opened with the lever. Mainly used for drainage of fuel diesel tanks.

These valves are installed so that the medium flows directly over the disc.

Features & Benefits

- 3.1 certificates available on request
- Flanged PN16 (others on request)
- Optional blocking device to prevent accidental operation

Pressure & Temperature

Pressure range:-
Up to 16 Bar

Temperature Range:-
Up to 90°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
A	90	95	100	105	115	125	145	155	175
B (261004)	150	155	155	155	185	190	220	215	280
C (261002)	115	115	125	130	135	145	160	165	195
D	95	105	115	140	150	165	185	200	220
E	160	160	160	160	160	160	160	160	210
Weight Kg	3.9	4.6	5.4	7.1	9.6	12.5	17.6		

STANDARD MATERIALS (Others available on request)

Body/Bonnet	Ductile Iron (GGG40)
Disc & Stem	Stainless Steel (X14CrMoS 17)
Spring	Stainless Steel (X10CrNi18-8)
O-Ring	FKM
Seat Ring	Stainless Steel (X12Cr 13)
Hand Lever	Stainless Steel (X5CrNi18-10)
Handwheel	Cast Iron (GG25)

Do you require class approved valves? Contact sales for availability.

